

MATERIAL SAFETY DATA SHEET

EPOXY WELDKIT / BUTT-WRAP KIT PART B

I. 24-HOUR EMERGENCY CONTACT INFORMATION

CHEM-TEL United States.....800-255-3924
 International.....813-248-0585

II. HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Component Identification	CASRN	OSHA PEL	ACGIH TLV	% (by weight)
Amine Mixture	Proprietary	None Established		100

Product Description.....AMINE

III. PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point..... > 572°F (300°C)
 Melting Point..... Not Determined
 Vapor Pressure..... Not Determined
 Vapor Density (Air = 1)..... <10
 Specific Gravity (Water = 1)..... ~1
 Evaporation Rate (butyl acetate = 1)..... Not Determined
 pH..... Not Determined, Corrosive
 Appearance and Odor..... Amber Liquid, Irritating Odor
 Odor Threshold..... Not Determined

IV. FIRE and EXPLOSION HAZARDS

Flash Point..... >200°F (93°C), Pensky-Martens Closed Cup
 Autoignition Temperature..... Not Determined
 LEL / UEL..... Not Determined
 Extinguishing Media..... Dry Chemical, CO₂, Water Fog, Alcohol Foam
 NFPA Ratings..... Health (3) – Flammability (1) – Reactivity (1)

Special Firefighting Procedures: Do not direct a solid stream of water into hot burning polls, this may cause frothing and increase fire intensity. Use self-contained breathing apparatus and protective clothing.

Fire and Explosion Hazards: During a fire, oxides of nitrogen may be produced.

V. REACTIVITY DATA

Stability..... Stable
 Hazardous Polymerization..... Will not occur
 Conditions to Avoid..... Do not mix with nirates or other nitrosating agents
 Incompatibilities..... Oxidizes
 Hazardous Decomposition Products..... NO_x, CO and CO₂

VI. HEALTH HAZARD DATA

Route(s) of Entry: Inhalation.....Yes
Skin.....Yes
Ingestion.....Not Expected

Acute (Short-Term) Health Effects: Product vapor in low concentrations can cause lacrimation, conjunctivitis, and corneal edema when absorbed into the tissue of the eye from the atmosphere. Corneal edema may give rise to a perception of "blue haze" or "blue fog" around lights. This result is transient and has no known residual effect. Burns of the eye may cause blindness. Contact of undiluted product with eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis, or permanent injury. Inhalation of vapors may severely damage contacted tissue and produce scarring. Inhalation of aerosols and mists may severely damage contact-ed tissue and produce scarring. Product is absorbed through the skin and may cause nausea, headache, and general discomfort.

Chronic (Long-Term) Health Effects: Product may cause cancer after repeated exposure. Repeated and/or prolonged exposure may cause allergic reaction/sensitization. Repeated and/or prolonged exposure may result in liver disorders, respiratory effects, adverse eye effects, and adverse skin effects. Effects from inhalation of vapors may be delayed. Repeated and/or prolonged exposure to low concentrations of vapor may cause sore throat that is transient.

Carcinogenicity: None of the chemicals in this product are classified as known of potential human carcinogens by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), or OSHA.

Signs and Symptoms of Exposure: Signs and symptoms following exposure may include irritation and burning sensation to eyes, skin, and respiratory tract (if inhaled). Nausea, headache, and general discomfort may follow skin absorption.

Medical Conditions Generally Aggravated by Exposure: Asthma, chronic respiratory diseases, eye diseases, liver disorders, and skin disorders and allergies.

Emergency and First Aid Procedures:

- Inhalation:* Remove to fresh air if exposure symptoms develop and seek medical attention.
- Skin Contact:* Gently wash all affected skin areas thoroughly with water soap and water while removing contaminated clothing. If irritation persists or burning sensation is evident, seek medical attention.
- Eye Contact:* Flush eyes with water for 20 to 30 minutes. Obtain prompt medical attention, preferably from an ophthalmologist.
- Ingestion:* Not expected under normal use conditions. However, if ingestion does occur, do not induce vomiting. Give large amounts of water or milk and seek medical attention.

HMIS Ratings.....Health (3) – Flammability (1) – Reactivity (1)

VII. PRECAUTIONS FOR SAFE HANDLING and USE

Steps to be Taken in Case Material is Released or Spill: Due to the relatively small end-use container sizes, significant spills are unlikely. However, if a spill does occur, collect and place into a suitable container for disposal. Do not allow spilled materials to enter storm sewers, sanitary sewers, or impact ground water.

Waste Disposal Method: Disposal must be in accordance with applicable laws.

Precautions to be Taken in Handling and Storage: Copper and copper alloys should not be used for storage as the product may quickly corrode them.

VIII. CONTROL MEASURES

Respiratory Protection: None typically required for normal use. Self-contained breathing apparatus may be needed if product is used in a confined or poorly ventilated area.

Ventilation: A system of local and/or general exhaust is recommended.

Hand Protection: Gloves impervious to this material should be worn.

Eye Protection: ANSI-approved safety glasses with side shields or chemical goggles.

Other: Such clothing as to minimize or eliminate skin contact.

IX. REGULATORY INFORMATION (Not meant to be all-inclusive)

Hazardous Materials Transportation Act (HMTA)

When offered alone, this material should be classified as follows:

Proper Shipping Name.....Amines, Liquid, Corrosive, n.o.s., Mixture
 (4,4'-Methylenebicyclohexanamine)
 Hazard Class.....8
 Identification Number.....UN2735
 Packing Group.....II
 Label Required.....Corrosive

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

This produce contains the following CERCLA Section 102(a) hazardous substance(s) as listed in 40 CFR 302.4:

Identity	CASRN	% (by weight)	Reportable Quantity (RQ)
None			

Superfund Amendment and Reauthorization Act (SARA)

This product contains the following SARA Title III Section 302 extremely hazardous substance(s) as listed in 40 CFR Part 355:

Identity	CASRN	% (by weight)
None		

SARA Title III Section 311/312 hazardous categorization:

This product has been reviewed according to the EPA hazard categories promulgated under SARA Title III Section 311 and 312 and is considered to meet the following hazard categories:

- An immediate (acute) health hazard
- A delayed (chronic) health hazard

This product contains the following SARA Title III Section 313 toxic substance(s) as listed in 40 CFR Part 372:

Identity	CASRN	% (by weight)
None		

Toxic Substances Control Act (TSCA)

All ingredients are on the TSCA inventory or are not required to be on the inventory.

CATALYST / HARDENER INDEX

The material described in the MSDS is intended for use with the following:

EPOXY WELDKIT / BUTT-WRAP KIT PART A

Review literature supplied with product or contact NOV Fiber Glass Systems for proper mixing ratios.

National Oilwell Varco has produced this brochure for general information only, and it is not intended for design purposes. Although every effort has been made to maintain the accuracy and reliability of its contents, National Oilwell Varco in no way assumes responsibility for liability for any loss, damage or injury resulting from the use of information and data herein nor is any warranty expressed or implied. Always cross-reference the bulletin date with the most current version listed at the web site noted in this literature.

North America

17115 San Pedro Ave. Suite 200
San Antonio, Texas 78232 USA
Phone: 210 477 7500

South America

Avenida Fernando Simoes
Recife, Brazil 51020-390
Phone: 55 31 3501 0023

Europe

P.O. Box 6, 4190 CA
Geldermalsen, The Netherlands
Phone: 31 345 587 587

Asia Pacific

No. 7A, Tuas Avenue 3
Jurong, Singapore 639407
Phone: 65 6861 6118

Middle East

P.O. Box 17324
Dubai, UAE
Phone: 971 4881 3566